

# ***SPATIAL ENHANCE EFFECT***



Dimmable



Ra>90



UGR<19



Superior Visual Comfort



Recessable & Adjustable



LED Spotlight PA YA FLEX



Dimmable



Ra>90



UGR<19



Superior Visual Comfort



Recessable & Adjustable

## Specification

Item Code	Item Description	Power (W)	Efficacy (lm/W)	CCT (K)	Beam Angle
541003478100	LEDSpot-P2-LTH01040009-FLEX-125-40W-15°-935-BLE2-D	40	100	3500	15°
541003478200	LEDSpot-P2-LTH01040009-FLEX-125-40W-24°-935-BLE2-D	40	100	3500	24°
541003478300	LEDSpot-P2-LTH01040009-FLEX-125-40W-36°-935-BLE2-D	40	100	3500	36°

## Accessories

Item Code	Item Description
820004009400	Driver-OP-IDSCC0401100B1-01-40W-9-42V-BLE2-D

Technical Specifications	
Life Time (L70B50)	30000
Colour Consistency (SDCM)	<5
Housing Color	White
Ra	>90
Degree of protection (IP)	IP20
Driver Integrated	No
Protection Class	III
Power Factor	0.9

Electrical Supply	
Frequency	50/60Hz
Nominal Voltage	40/240(driver)

Mechanical and Finishing Properties	
Housing Material	Aluminium
Optical Material	PMMA

Ambient Conditions	
Operating Temperature	-20-40°C

## Packaging Information

Item		Outer box		
Item Code	Item Description	Dimensions(mm) (LxWxH)	Gross Weight (kg)	Packing Qty (pcs/CTN)
541003478100	LEDSpot-P2-LTH01040009-FLEX-125-40W-15°-935-BLE2-D	300*300*405	7.192	8
541003478200	LEDSpot-P2-LTH01040009-FLEX-125-40W-24°-935-BLE2-D	300*300*405	7.192	8
541003478300	LEDSpot-P2-LTH01040009-FLEX-125-40W-36°-935-BLE2-D	300*300*405	7.192	8
820004009400	Driver-OP-IDSCC0401100B1-01-40W-9-42V-BLE2-D	315*240*225	6.24	40

## Dimensional Drawing (mm)

